

SP-90 Dry Film Silicone Lubricant



SP-90 Silicone lubricant spray is a superior silicone dry lubricant formulated to provide extra performance and maximum silicone release. SP-90 provides a quick drying time and is clean and easy-to-use and provides protection against corrosion. SP-90 is an advanced silicone formulation that stops squeaks and decreases friction. SP-90 is non-staining and has low odour. SP-90 is ideal for use as a mould release or dry lubricant on any steel, plastic, glass, rubber, vinyl, and wooden surfaces. SP-90 is long lasting and has a wide temperature range -40°C to 250°C. SP-90 is ideal for use on coin operated machines. SP-90 contains anti static which prevents the build up of dust or other particles. A non stick mould release agent with extra high silicone content makes SP-90 ideal for use in the plastic moulding trade. SP-90 makes joinery and wood working projects easy by applying a light coat onto machine tool beds or saw blades for easy cutting and a low drag. Spray hand saws for easy cutting of wet wood. Spray onto screw threads for easy power diving and to reduce 'cam out'. SP-90 is ideal as a thread lubricant in the sewing industry, the leather, and shoe trades.



500 ml Aerosol Product Code 1887



Key Features:

- Superior non toxic maximum silicone lubricant
- Clear, clean, and dry lubricating film
- Low odour and non staining lubricant spray
- Reduces friction and static
- Stable over a wide temperature Prevents sticking of rubber or plastic parts
- Protects against corrosion and oxidation
- Ideal for use on rubber, plastics, metal, vinyl, and glass



Application(s):

- Anti-seize, Assembly & Dismantle
- Silicone Lubricant
- Release Fluids
- Plumbing Products

Action Can Ltd.

Dixon Close, Old Boston Trading Estate, Haydock, St. Helens, England, WA11 9SF
Tel: 00 44 (0)1942 713667 Fax: 00 44 (0)1942 716235
Email: salesoffice@actioncan.com www.actioncan.com



Certificate No. 768